

## Preliminary datasheet

### EasyPACK™ module with CoolSiC™ Trench MOSFET and PressFIT / NTC

#### Features

- Electrical features
  - $V_{DSS} = 1200\text{ V}$
  - $I_{DN} = 50\text{ A} / I_{DRM} = 100\text{ A}$
  - Low inductive design
  - High current density
- Mechanical features
  - PressFIT contact technology
  - Integrated NTC temperature sensor
  - Rugged mounting due to integrated mounting clamps



Typical appearance


#### Potential applications

- Solar applications

#### Product validation

- Qualified for industrial applications according to the relevant tests of IEC 60747, 60749 and 60068

#### Description



## Table of contents

	<b>Description</b> .....	1
	<b>Features</b> .....	1
	<b>Potential applications</b> .....	1
	<b>Product validation</b> .....	1
	<b>Table of contents</b> .....	2
<b>1</b>	<b>Package</b> .....	3
<b>2</b>	<b>MOSFET</b> .....	3
<b>3</b>	<b>Body diode</b> .....	5
<b>4</b>	<b>Diode, Boost</b> .....	6
<b>5</b>	<b>Bypass-diode</b> .....	6
<b>6</b>	<b>Inverse-polarity protection diode</b> .....	7
<b>7</b>	<b>NTC-Thermistor</b> .....	8
<b>8</b>	<b>Characteristics diagrams</b> .....	9
<b>9</b>	<b>Circuit diagram</b> .....	16
<b>10</b>	<b>Package outlines</b> .....	17
<b>11</b>	<b>Module label code</b> .....	18
	<b>Revision history</b> .....	19
	<b>Disclaimer</b> .....	20

## 1 Package

**Table 1** Insulation coordination

Parameter	Symbol	Note or test condition	Values	Unit
Isolation test voltage	$V_{ISOL}$	RMS, $f = 50$ Hz, $t = 60$ min	3.0	kV
Internal isolation		basic insulation (class 1, IEC 61140)	$Al_2O_3$	
Comparative tracking index	$CTI$		> 200	
Relative thermal index (electrical)	$RTI$	housing	140	°C

**Table 2** Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Stray inductance module	$L_{sCE}$			10		nH
Module lead resistance, terminals - chip	$R_{AA'+CC'}$	$T_H = 25$ °C, per switch		3		mΩ
Module lead resistance, terminals - chip	$R_{CC'+EE'}$	$T_H = 25$ °C, per switch		2		mΩ
Storage temperature	$T_{stg}$		-40		125	°C
Mounting force per clamp	$F$		20		50	N
Weight	$G$			24		g

Note: The current under continuous operation is limited to 25 A rms per connector pin.

## 2 MOSFET

**Table 3** Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit
Drain-source voltage	$V_{DSS}$	$T_{vj} = 25$ °C	1200	V
Implemented drain current	$I_{DN}$		50	A
Continuous DC drain current	$I_{DDC}$	$T_{vj} = 175$ °C, $V_{GS} = 18$ V $T_H = 65$ °C	45	A
Repetitive peak drain current	$I_{DRM}$	verified by design, $t_p$ limited by $T_{vjmax}$	100	A
Gate-source voltage, max. transient voltage	$V_{GS}$	$D < 0.01$	-10/23	V
Gate-source voltage, max. static voltage	$V_{GS}$		-7/20	V

**Table 4 Recommended values**

Parameter	Symbol	Note or test condition	Values	Unit
On-state gate voltage	$V_{GS(on)}$		15...18	V
Off-state gate voltage	$V_{GS(off)}$		-5...0	V

**Table 5 Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit	
			Min.	Typ.	Max.		
Drain-source on-resistance	$R_{DS(on)}$	$I_D = 50\text{ A}$	$V_{GS} = 18\text{ V}, T_{vj} = 25\text{ °C}$		16.2		mΩ
			$V_{GS} = 18\text{ V}, T_{vj} = 125\text{ °C}$		26.1		
			$V_{GS} = 18\text{ V}, T_{vj} = 175\text{ °C}$		34.7		
			$V_{GS} = 15\text{ V}, T_{vj} = 25\text{ °C}$		19.4		
Gate threshold voltage	$V_{GS(th)}$	$I_D = 20\text{ mA}, V_{DS} = V_{GS}, T_{vj} = 25\text{ °C},$ (tested after 1ms pulse at $V_{GS} = +20\text{ V}$ )	3.45	4.3	5.15	V	
Total gate charge	$Q_G$	$V_{DD} = 800\text{ V}, V_{GS} = -3/18\text{ V}$		0.149		μC	
Internal gate resistor	$R_{Gint}$	$T_{vj} = 25\text{ °C}$		4.1		Ω	
Input capacitance	$C_{ISS}$	$f = 0\text{ kHz}, V_{DS} = 800\text{ V}, V_{GS} = 0\text{ V}$		4.4		nF	
Output capacitance	$C_{OSS}$	$f = 0\text{ kHz}, V_{DS} = 800\text{ V}, V_{GS} = 0\text{ V}$		0.21		nF	
Reverse transfer capacitance	$C_{RSS}$	$f = 0\text{ kHz}, V_{DS} = 800\text{ V}, V_{GS} = 0\text{ V}$		0.014		nF	
$C_{OSS}$ stored energy	$E_{OSS}$	$V_{DS} = 800\text{ V}, V_{GS} = -3/18\text{ V}, T_{vj} = 25\text{ °C}$		86		μJ	
Drain-source leakage current	$I_{DSS}$	$V_{DS} = 1200\text{ V}, V_{GS} = -3\text{ V}$		0.03	210	μA	
Gate-source leakage current	$I_{GSS}$	$V_{DS} = 0\text{ V}, T_{vj} = 25\text{ °C}$			400	nA	
Turn-on delay time (inductive load)	$t_{d\ on}$	$I_D = 50\text{ A}, R_{Gon} = 3.3\text{ Ω}, V_{DD} = 600\text{ V}, V_{GS} = -3/18\text{ V}$	$T_{vj} = 25\text{ °C}$		32		ns
			$T_{vj} = 125\text{ °C}$		32		
			$T_{vj} = 175\text{ °C}$		32		
Rise time (inductive load)	$t_r$	$I_D = 50\text{ A}, R_{Gon} = 3.3\text{ Ω}, V_{DD} = 600\text{ V}, V_{GS} = -3/18\text{ V}$	$T_{vj} = 25\text{ °C}$		23.9		ns
			$T_{vj} = 125\text{ °C}$		23.9		
			$T_{vj} = 175\text{ °C}$		23.9		

**(table continues...)**

**Table 5 (continued) Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Turn-off delay time (inductive load)	$t_{d\ off}$	$I_D = 50\ A, R_{Goff} = 2\ \Omega, V_{DD} = 600\ V, V_{GS} = -3/18\ V$	$T_{vj} = 25\ ^\circ C$	60.7		ns
			$T_{vj} = 125\ ^\circ C$	60.7		
			$T_{vj} = 175\ ^\circ C$	60.7		
Fall time (inductive load)	$t_f$	$I_D = 50\ A, R_{Goff} = 2\ \Omega, V_{DD} = 600\ V, V_{GS} = -3/18\ V$	$T_{vj} = 25\ ^\circ C$	10.5		ns
			$T_{vj} = 125\ ^\circ C$	10.5		
			$T_{vj} = 175\ ^\circ C$	10.5		
Turn-on energy loss per pulse	$E_{on}$	$I_D = 50\ A, V_{DD} = 600\ V, L_\sigma = 35\ nH, V_{GS} = -3/18\ V, R_{Gon} = 3.3\ \Omega, di/dt = 4.29\ kA/\mu s (T_{vj} = 175\ ^\circ C)$	$T_{vj} = 25\ ^\circ C$	0.516		mJ
			$T_{vj} = 125\ ^\circ C$	0.516		
			$T_{vj} = 175\ ^\circ C$	0.516		
Turn-off energy loss per pulse	$E_{off}$	$I_D = 50\ A, V_{DD} = 600\ V, L_\sigma = 35\ nH, V_{GS} = -3/18\ V, R_{Goff} = 2\ \Omega, dv/dt = 45.7\ kV/\mu s (T_{vj} = 175\ ^\circ C)$	$T_{vj} = 25\ ^\circ C$	0.133		mJ
			$T_{vj} = 125\ ^\circ C$	0.133		
			$T_{vj} = 175\ ^\circ C$	0.133		
Thermal resistance, junction to heat sink	$R_{thJH}$	per MOSFET		1.1		K/W
Temperature under switching conditions	$T_{vj\ op}$		-40		175	$^\circ C$

Note: The selection of positive and negative gate-source voltages impacts losses and the long-term behavior of the MOSFET and body diode. The design guidelines described in Application Notes AN 2018-09 and AN 2021-13 must be considered to ensure sound operation of the device over the planned lifetime.

$T_{vj,op} > 150\ ^\circ C$  is allowed for operation at overload conditions for MOSFET and body diode. For detailed specifications, please refer to AN 2021-13.

### 3 Body diode

**Table 6 Maximum rated values**

Parameter	Symbol	Note or test condition	Values	Unit
DC body diode forward current	$I_{SD}$	$T_{vj} = 175\ ^\circ C, V_{GS} = -3\ V, T_H = 65\ ^\circ C$	24	A

**Table 7 Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	$V_{SD}$	$I_{SD} = 50\ A, V_{GS} = -3\ V$	$T_{vj} = 25\ ^\circ C$	4.2	5.35	V
			$T_{vj} = 125\ ^\circ C$	3.9		
			$T_{vj} = 175\ ^\circ C$	3.8		

## 4 Diode, Boost

**Table 8** Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit	
Repetitive peak reverse voltage	$V_{RRM}$	$T_{vj} = 25\text{ °C}$	1200	V	
Continuous DC forward current	$I_F$		40	A	
Repetitive peak forward current	$I_{FRM}$	$t_p = 1\text{ ms}$	80	A	
$I^2t$ - value	$I^2t$	$t_p = 10\text{ ms}, V_R = 0\text{ V}$	$T_{vj} = 125\text{ °C}$	320	A <sup>2</sup> s
			$T_{vj} = 150\text{ °C}$	295	

**Table 9** Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	$V_F$	$I_F = 40\text{ A}, V_{GE} = 0\text{ V}$	$T_{vj} = 25\text{ °C}$	1.40	1.85	V
			$T_{vj} = 125\text{ °C}$	1.70		
			$T_{vj} = 150\text{ °C}$	1.85		
Peak reverse recovery current	$I_{RM}$	$V_{CC} = 600\text{ V}, I_F = 40\text{ A}, -di_F/dt = 3900\text{ A}/\mu\text{s} (T_{vj} = 150\text{ °C})$	$T_{vj} = 25\text{ °C}$	43		A
			$T_{vj} = 125\text{ °C}$	43		
			$T_{vj} = 150\text{ °C}$	43		
Recovered charge	$Q_r$	$V_{CC} = 600\text{ V}, I_F = 40\text{ A}, -di_F/dt = 3900\text{ A}/\mu\text{s} (T_{vj} = 150\text{ °C})$	$T_{vj} = 25\text{ °C}$	4.03		$\mu\text{C}$
			$T_{vj} = 125\text{ °C}$	4.03		
			$T_{vj} = 150\text{ °C}$	4.03		
Reverse recovery energy	$E_{rec}$	$V_{CC} = 600\text{ V}, I_F = 40\text{ A}, -di_F/dt = 3900\text{ A}/\mu\text{s} (T_{vj} = 150\text{ °C})$	$T_{vj} = 25\text{ °C}$	0.063		mJ
			$T_{vj} = 125\text{ °C}$	0.063		
			$T_{vj} = 150\text{ °C}$	0.063		
Thermal resistance, junction to heat sink	$R_{thJH}$	per diode	1.11		K/W	
Temperature under switching conditions	$T_{vj\text{ op}}$		-40	150	°C	

## 5 Bypass-diode

**Table 10** Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit
Repetitive peak reverse voltage	$V_{RRM}$	$T_{vj} = 25\text{ °C}$	1200	V

(table continues...)

**Table 10** (continued) Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit	
Maximum RMS forward current per chip	$I_{FRMSM}$	$T_H = 80\text{ °C}$	50	A	
Maximum RMS current at rectifier output	$I_{RMSM}$	$T_H = 80\text{ °C}$	50	A	
Surge forward current	$I_{FSM}$	$t_p = 10\text{ ms}$	$T_{vj} = 25\text{ °C}$	450	A
			$T_{vj} = 150\text{ °C}$	360	
$I^2t$ - value	$I^2t$	$t_p = 10\text{ ms}$	$T_{vj} = 25\text{ °C}$	1010	A <sup>2</sup> s
			$T_{vj} = 150\text{ °C}$	648	

**Table 11** Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	$V_F$	$I_F = 30\text{ A}$ , $T_{vj} = 150\text{ °C}$		0.95		V
Reverse current	$I_r$	$T_{vj} = 150\text{ °C}$ , $V_R = 1200\text{ V}$		0.1		mA
Thermal resistance, junction to heat sink	$R_{thJH}$	per diode		1.29		K/W
Temperature under switching conditions	$T_{vj, op}$		-40		150	°C

## 6 Inverse-polarity protection diode

**Table 12** Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit	
Repetitive peak reverse voltage	$V_{RRM}$	$T_{vj} = 25\text{ °C}$	1200	V	
Maximum RMS forward current per chip	$I_{FRMSM}$	$T_H = 80\text{ °C}$	50	A	
Maximum RMS current at rectifier output	$I_{RMSM}$	$T_H = 80\text{ °C}$	50	A	
Surge forward current	$I_{FSM}$	$t_p = 10\text{ ms}$	$T_{vj} = 25\text{ °C}$	450	A
			$T_{vj} = 150\text{ °C}$	360	
$I^2t$ - value	$I^2t$	$t_p = 10\text{ ms}$	$T_{vj} = 25\text{ °C}$	1010	A <sup>2</sup> s
			$T_{vj} = 150\text{ °C}$	648	

**Table 13** Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	$V_F$	$I_F = 30 \text{ A}$ $T_{vj} = 150 \text{ °C}$		0.95		V
Reverse current	$I_r$	$T_{vj} = 150 \text{ °C}$ , $V_R = 1200 \text{ V}$		0.1		mA
Thermal resistance, junction to heat sink	$R_{thJH}$	per diode		1.16		K/W
Temperature under switching conditions	$T_{vj, op}$		-40		150	°C

## 7 NTC-Thermistor

**Table 14** Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Rated resistance	$R_{25}$	$T_{NTC} = 25 \text{ °C}$		5		kΩ
Deviation of $R_{100}$	$\Delta R/R$	$T_{NTC} = 100 \text{ °C}$ , $R_{100} = 493 \text{ Ω}$	-5		5	%
Power dissipation	$P_{25}$	$T_{NTC} = 25 \text{ °C}$			20	mW
B-value	$B_{25/50}$	$R_2 = R_{25} \exp[B_{25/50}(1/T_2 - 1/(298,15 \text{ K}))]$		3375		K
B-value	$B_{25/80}$	$R_2 = R_{25} \exp[B_{25/80}(1/T_2 - 1/(298,15 \text{ K}))]$		3411		K
B-value	$B_{25/100}$	$R_2 = R_{25} \exp[B_{25/100}(1/T_2 - 1/(298,15 \text{ K}))]$		3433		K


Note: Specification according to the valid application note.



## 8 Characteristics diagrams


**Output characteristic (typical), MOSFET**

$I_D = f(V_{DS})$   
 $V_{GS} = 18\text{ V}$




**Output characteristic (typical), MOSFET**

$I_D = f(V_{DS})$   
 $V_{GS} = 15\text{ V}$




**Drain source on-resistance (typical), MOSFET**

$R_{DS(on)} = f(I_D)$   
 $V_{GS} = 18\text{ V}$




**Drain source on-resistance (typical), MOSFET**

$R_{DS(on)} = f(T_{vj})$   
 $I_D = 50\text{ A}$




**Output characteristic field (typical), MOSFET**

$I_D = f(V_{DS})$   
 $T_{vj} = 175\text{ °C}$




**Transfer characteristic (typical), MOSFET**

$I_D = f(V_{GS})$   
 $V_{DS} = 20\text{ V}$




**Gate-source threshold voltage (typical), MOSFET**

$V_{GS(th)} = f(T_{vj})$   
 $V_{GS} = V_{DS}$



**Gate charge characteristic (typical), MOSFET**


$V_{GS} = f(Q_G)$   
 $I_D = 50\text{ A}, T_{vj} = 25\text{ °C}$



**Capacity characteristic (typical), MOSFET**

$C = f(V_{DS})$


$f = 100 \text{ kHz}$ ,  $T_{vj} = 25 \text{ °C}$ ,  $V_{GS} = 0 \text{ V}$



**Forward characteristic body diode (typical), MOSFET**

$I_{SD} = f(V_{SD})$


$T_{vj} = 25 \text{ °C}$



**Forward characteristic body diode (typical), MOSFET**

$V_{SD} = f(T_{vj})$


$I_{SD} = 50 \text{ A}$



**Switching losses (typical), MOSFET**

$E = f(I_D)$


$R_{Goff} = 2 \text{ } \Omega$ ,  $R_{Gon} = 3.3 \text{ } \Omega$ ,  $V_{DD} = 600 \text{ V}$ ,  $V_{GS} = -3/18 \text{ V}$



**Switching losses (typical), MOSFET**

$E = f(R_G)$


$V_{DD} = 600\text{ V}, I_D = 50\text{ A}, V_{GS} = -3/18\text{ V}$



**Switching times (typical), MOSFET**

$t = f(I_D)$


$R_{Goff} = 2\ \Omega, R_{Gon} = 3.3\ \Omega, V_{DD} = 600\text{ V}, T_{vj} = 175\ \text{°C}, V_{GS} = -3/18\text{ V}$



**Switching times (typical), MOSFET**

$t = f(R_G)$


$V_{DD} = 600\text{ V}, I_D = 50\text{ A}, T_{vj} = 175\ \text{°C}, V_{GS} = -3/18\text{ V}$



**Current slope (typical), MOSFET**

$di/dt = f(R_G)$


$V_{DD} = 600\text{ V}, I_D = 50\text{ A}, V_{GS} = -3/18\text{ V}$



**Voltage slope (typical), MOSFET**

$dv/dt = f(R_G)$


$V_{DD} = 600\text{ V}, I_D = 50\text{ A}, V_{GS} = -3/18\text{ V}$



**Reverse bias safe operating area (RBSOA), MOSFET**


$I_D = f(V_{DS})$

$R_{Goff} = 2\ \Omega, T_{vj} = 175\ \text{°C}, V_{GS} = -3/18\ \text{V}$




**Transient thermal impedance, MOSFET**

$Z_{th} = f(t)$




**Forward characteristic (typical), Diode, Boost**

$I_F = f(V_F)$




**Switching losses (typical), Diode, Boost**

$E_{rec} = f(I_F)$   
 $R_{Gon} = 3.3 \Omega, V_{CC} = 600 V$




**Switching losses (typical), Diode, Boost**

$E_{rec} = f(R_G)$   
 $I_F = 40 A, V_{CC} = 600 V$




**Transient thermal impedance, Diode, Boost**

$Z_{th} = f(t)$




**Forward characteristic (typical), Bypass-diode**

$I_F = f(V_F)$




**Transient thermal impedance, Bypass-diode**

$Z_{th} = f(t)$




**Forward characteristic (typical), Inverse-polarity protection diode**

$I_F = f(V_F)$




**Transient thermal impedance, Inverse-polarity protection diode**

$Z_{th} = f(t)$



**Temperature characteristic (typical), NTC-Thermistor**

$R = f(T_{NTC})$



## 9 Circuit diagram




Figure 1



10 Package outlines




Figure 2

## 11 Module label code



Module label code			
Code format	Data Matrix	Barcode Code128	
Encoding	ASCII text	Code Set A	
Symbol size	16x16	23 digits	
Standard	IEC24720 and IEC16022	IEC8859-1	
Code content	<i>Content</i>	<i>Digit</i>	<i>Example</i>
	Module serial number	1 - 5	71549
	Module material number	6 - 11	142846
	Production order number	12 - 19	55054991
	Date code (production year)	20 - 21	15
	Date code (production week)	22 - 23	30
Example	 		
	71549142846550549911530		71549142846550549911530

Figure 3

## Revision history

Document version	Date of release	Description of changes
0.10	2022-11-21	Initial version

## Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

**Edition 2022-11-21**

**Published by**

**Infineon Technologies AG**

**81726 Munich, Germany**

**© 2022 Infineon Technologies AG**

**All Rights Reserved.**

**Do you have a question about any aspect of this document?**

**Email: [erratum@infineon.com](mailto:erratum@infineon.com)**

**Document reference**

**IFX-ABE526-001**

## Important notice

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

## Warnings

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.